

DS-1H18S/E-E HD Video Balun



Features and Functions


- Screw interface with cable and without cable
- Mini size for easy installation
- ABS outer shell for convenient to use in intensive project
- No power required, and simplified project wiring
- Plug and play, real-time transmit CCTV HD video signal, and high quality and stable video
- Compatible with HDTV/HDCVI/AHD
- Transmission distance: non-POC Camera: Max. 200m.
- Superior anti-interference and lightning protection and ESD



Specifications

Model		DS-1H18S/E-E
Properties	Transmission Signal	1 channel
	Transmission Distance	Non-POC Camera: Max 200m
	Category Type	UTP CAT 5E/ 6 (R<100Ω/100M)
Video Transmission Properties and Port	Coaxial Video Connector	BNC-M
	Twisted-pair Video Connector	Screw Interface
	Compatible Format	HDTVI/HDCVI/AHD
	Resolution	720P/1080P/3MP/4MP/5MP
	Ant-interference	>60db
Protection	ESD	1a contact discharge electricity level3
		1b air discharge electricity level3
		Per: IEC61000-4-2
	Coaxial Cable Connector	2KV(common-code) Per:IEC61000-4-5
UTP Cable Connector	2KV(different-code), 2KV(common-code) Per:IEC61000-4-5	
Impedance	BNC Male	75 ohms
	UTP Cable	100 ohms
Physical Properties	Shell	ABS
	Color	Black
	Dimensions (L x W x H)	147mm x 14.5mmx 17mm
		45mm x 14.5mmx 17mm
Weight	31.2 g	
Stability	MTBF	>10000 h
Environmental	Operating Temperature	-10-55°C
	Storage Temperature	-20-70°C
	Humidity	0-95% (non-condensing)

Typical Application



Available Model

DS-1H18S/E-E

Distributed by



HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Africa
T +27 (0) 0351172
sale.africa@hikvision.com

Hikvision Hong Kong
T +852-2151-1761